

MODELLING THE ROOT GROWTH: AN OPTIMAL CONTROL APPROACH TO LINK BIOLOGY AND ROBOTICS

Fabio Tedone

Jointly with M. Palladino, E. Del Dottore, B. Mazzolai, P. Marcati




11th Conference on Dynamical Systems Applied to Biology and
Natural Sciences
Trento, February 7, 2020

PLANT-INSPIRED ROBOTS

Complex behaviour


- an activity that requires many **decisions and actions**, in rapid order or simultaneously;
- an activity adopted to **interact** with other organisms and the environment.



CIRCUMNUTATION


F. Tedone, E. Del Dottore, M. Palladino, B. Mazzolai, P. Marcati,

Optimal control of plant root tip dynamics in soil, submitted



- **Circumnutation** is an elliptical, circular or pendulum like movement;
- Root circumnutation helps **to reduce soil friction (Fisher, 1964)**;
- **Soil complexity** and different **plant genotypes** make difficult to isolate and study this behaviour (**Bester and Behringe, 2017**);
- To characterise the root circumnutation and **design robots for soil exploration**;
- Modelling of **dynamical** soil-root interactions (**Kolbe, 2017**).

THE MODEL



- x position of the tip;
- v velocity of the tip;
- u control function driving the motion;
- α amplitude of the circumnutation;
- k density from 0 to a fully compressed soil k^{\max} ;
- F_s^{\max} maximum resistance offered by a compressed soil;
- R function to estimate rearrangement of soil particles.



THE MODEL

$$\begin{cases} \dot{x}(t) = v(t), & t \in [t_0, T_f] \\ \dot{v}(t) = u(1 - F_s) - F_d \\ (x(t_0), v(t_0)) = (x_0, v_0) \in \mathbb{R}^6, \\ t_0 \geq 0, & T_f \geq t_0 \end{cases}$$

$$W = \int_{t_0}^{T_f} |\langle u, v \rangle| ds;$$


$$F_s(t, v, u) = F_s^{\max} \frac{k}{k_{\max}} R(t, v, u);$$

$$F_d(t, v, u) \propto R(t, v, u)v.$$



PARAMETER ESTIMATION


- Constant speed, **straight** descent path;
- Constant speed, **helical circumnutating** descent path;
- Three different densities in **real soil**.



Up to 33% of energy saved by the **circumnutation** with respect to the straight penetration.

E. Del Dottore et al., *An efficient soil penetration strategy for explorative robots inspired by plant root circumnutation movements*, Bioinspiration & Biomimetics, 2017

THE OPTIMAL CONTROL BASED APPROACH: RESULTS



- Greater oscillations of the optimal trajectory in lower dense soils (**Dexter and Hewitt, 1978, Del Dottore et al., 2016**);
- The amplitude **continuously oscillates** around an optimal value.
- Minimum improvement of 0.16% with respect previous experiments.
- Takes into account **the size** of the tip to support the design of robotic devices;

EFFICIENCY OF MECHANICAL MOTION PATTERNS

F. Tedone, M. Palladino,

Hamilton-Jacobi-Bellman Equation for Control Systems with Friction, submitted

Relaxing the hypothesis...

- Presence of sensors on the robotic tip:
No regular shape and computation of the interacting surface;
- No homogeneous soil:
Need to average local soil friction effects;
- Increasing speed for robotic devices:
The drag force may not depend linearly on the speed

$$F_d \propto R(t)f(|v|)\frac{v}{|v|};$$

EFFICIENCY OF MECHANICAL MOTION PATTERNS

F. Tedone, M. Palladino,

Hamilton-Jacobi-Bellman Equation for Control Systems with Friction, submitted

Relaxing the hypothesis...

- Presence of sensors on the robotic tip:
No regular shape and computation of the interacting surface;
- No homogeneous soil:
Need to average local soil friction effects;
- Increasing speed for robotic devices:
The drag force may not depend linearly on the speed

$$F_d \propto R(t)f(|v|)\frac{v}{|v|};$$


- The dynamics is not Lipschitz \rightarrow

Well-posedness?

Existence of minimum solutions?

MATHEMATICAL FRAMEWORK

A vector field $g(t, x)$ is applied to a rigid body \mathcal{B} at x . The friction $l(t, x)$ depends on the **surface of friction** of the rigid body \mathcal{B} .



$\eta(x)$ is the normal to \mathcal{B} , **transported** along S by $Q(\alpha)$.

We are computing an **average friction**.


$$\dot{x} = g(t, x) - l(t, x);$$

$$l(t, x) = \sum_i k(g(t, x), \alpha_i) \eta(x) \cdot Q(\alpha_i);$$

$$\dot{x} \in g(t, x) - \int_A k(g(t, x), \alpha) \partial_x \varphi(x, \alpha) \mu(d\alpha).$$

MATHEMATICAL FRAMEWORK

A vector field $g(t, x)$ is applied to a rigid body \mathcal{B} at x . The friction $l(t, x)$ depends on the **surface of friction** of the rigid body \mathcal{B} .



$\eta(x)$ is the normal to \mathcal{B} , **transported** along S by $Q(\alpha)$.

We are computing an **average friction**.

$$\dot{x} = g(t, x) - l(t, x);$$

$$l(t, x) = \sum_i k(g(t, x), \alpha_i) \eta(x) \cdot Q(\alpha_i);$$

$$\dot{x} \in g(t, x) - \int_A k(g(t, x), \alpha) \partial_x \varphi(x, \alpha) \mu(d\alpha).$$

If both the **vector field** g and the **friction strength** k depend on a **feedback control** u :

$$\dot{x} \in F(t, x, u) = g(t, x, u) - \int_A k(t, x, u, \alpha) \partial_x \varphi(x, \alpha) \mu(d\alpha)$$

Consider the **optimal control** problem:

$$(P_{t_0, x_0}) \left\{ \begin{array}{l} \text{Minimize } W(T, x(T)) \\ \text{over } T > t_0, (x, u) \in AC([t_0, T]; \mathbb{R}^n) \times \mathcal{U} \\ \dot{x}(t) \in F(t, x(t), u(t)), \text{ a.e } t \in [t_0, T] \\ u(t) \in U \subseteq \mathbb{R}^m, \text{ a.e } t \in [t_0, T] \\ x(t_0) = x_0 \in \mathbb{R}^n \\ (T, x(T)) \in \text{Gr}\mathcal{T} \subseteq \mathbb{R}^n \end{array} \right.$$

Aim: To characterise the **Value Function** $V(t_0, x_0) = \inf\{(P_{t_0, x_0})\}$.

PROPERTIES OF THE DYNAMICS

The dynamics represents a new class of

- **upper semi-continuous** controlled differential inclusions;
- **not** Lipschitz;
- with a possible **moving** target.

Proposition

$$\bar{F}(t, x) = \bigcup_u F(t, x, u)$$

The **dissipative** structure of the system allows to prove that \bar{F} is non-empty, compact and upper semi-continuous. \bar{F} is Lipschitz continuous w.r.t. t and One Sided Lipschitz ^a (OSL) w.r.t. x , uniformly w.r.t. t

^aT. Donchev, V. Rios, P. Wolenski, "Strong invariance and one-sided Lipschitz multifunctions", Nonlinear Anal.

Existence and uniqueness for any control and initial condition.

PROPERTIES OF THE OPTIMAL CONTROL PROBLEM

- Relaxed **growth condition** for the cost function $W \rightarrow$ Existence of minimisers.

PROPERTIES OF THE OPTIMAL CONTROL PROBLEM

- Relaxed **growth condition** for the cost function $W \rightarrow$ Existence of minimisers.

Define the **reachable** set

$$\mathcal{R}(T; t, x) := \{x(T) : \dot{x}(s) \in \bar{F}(s, x(s)), s \in [t, T], x(t) = x\}$$

and the set of **admissible trajectories** with initial condition $x(t) = x$:

$$\mathcal{A}(t, x) := \{(T, x(T)) \in \text{Gr}\mathcal{T} : x(T) \in \mathcal{R}(T; t, x), T \geq t\}.$$

- (GC)** Fix any $(t, x) \in \mathbb{R}^{1+n}$. For every $(T_k, x_k) \in \mathcal{A}(t, x)$ such that $T_k \rightarrow +\infty$, one has that $W(T_k, x_k) \rightarrow +\infty$.

GROWTH CONDITIONS

If one replaces **(GC)** with the following condition:

LGC For any $K \subset \mathbb{R}^{1+n}$ compact, there exists $\gamma > 0$ such that

$$W(t', x') \geq W(t, x) + \gamma(t' - t),$$

whenever $(t, x) \in K$, $(t', x') \in \mathcal{A}(t, x)$.

Then the related optimal solution stops **as soon as** it reaches the target.

GROWTH CONDITIONS

If one replaces **(GC)** with the following condition:

LGC For any $K \subset \mathbb{R}^{1+n}$ compact, there exists $\gamma > 0$ such that

$$W(t', x') \geq W(t, x) + \gamma(t' - t),$$

whenever $(t, x) \in K$, $(t', x') \in \mathcal{A}(t, x)$.

Then the related optimal solution stops **as soon as** it reaches the target.

(GC) does not imply optimal trajectory stops when it reaches the target.

INWARD POINTING CONDITION

(IPC) For any compact $G \subseteq \mathbb{R}^{1+n}$ there exists $\rho > 0$ such that, for all $(t, x) \in \partial \text{Gr}\mathcal{T} \cap G$

$$\min_{\xi \in \bar{F}(t,x)} \{l^0 + \langle l, \xi \rangle\} \leq -\rho \quad \text{for all } (l^0, l) \in N_{\text{Gr}\mathcal{T}}(t, x).$$

INWARD POINTING CONDITION

(IPC) For any compact $G \subseteq \mathbb{R}^{1+n}$ there exists $\rho > 0$ such that, for all $(t, x) \in \partial \text{Gr}\mathcal{T} \cap G$

$$\min_{\xi \in \bar{F}(t,x)} \{l^0 + \langle l, \xi \rangle\} \leq -\rho \quad \text{for all } (l^0, l) \in N_{\text{Gr}\mathcal{T}}(t, x).$$

$$\mathcal{D} = \{(t, x) \in \mathbb{R}^{1+n} : \mathcal{A}(t, x) \neq \emptyset\}$$

Inward Pointing Condition ensures:

\mathcal{D} is **open**;

the value function V is **locally Lipschitz** in \mathcal{D} .

INWARD POINTING CONDITION

(IPC) For any compact $G \subseteq \mathbb{R}^{1+n}$ there exists $\rho > 0$ such that, for all $(t, x) \in \partial\text{Gr}\mathcal{T} \cap G$

$$\min_{\xi \in \bar{F}(t,x)} \{l^0 + \langle l, \xi \rangle\} \leq -\rho \quad \text{for all } (l^0, l) \in N_{\text{Gr}\mathcal{T}}(t, x).$$

$$\mathcal{D} = \{(t, x) \in \mathbb{R}^{1+n} : \mathcal{A}(t, x) \neq \emptyset\}$$


Inward Pointing Condition ensures:

\mathcal{D} is **open**;

the value function V is **locally Lipschitz** in \mathcal{D} .

Small Time Controllability of the target.

DYNAMICAL PROGRAMMING PRINCIPLE




Bellman's principle of Optimality

The second part of an optimal trajectory is optimal.

Dynamic programming principle links the optimal control \bar{u} to the value function V :

- $V(t_0, x_0) \leq V(t, x(t))$ for all $t \in [t_0, T]$, $x(t)$ trajectory for some control $u(t)$;
- $V(t_0, x_0) = V(t, \bar{x}(t))$ for all $t \in [t_0, \bar{T}]$ iff $\bar{x}(t)$ is optimal in $[t_0, \bar{T}]$ with optimal control $\bar{u}(t)$;
- $V(t, x)$ satisfies an appropriate **Hamilton Jacobi Bellman (HJB)** equation.

INVARIANCE PRINCIPLES



Bellman's principle of Optimality

The second part of an optimal trajectory is optimal.

Introduce the minimised and the maximised **Hamiltonians**:

$$h(t, x, \eta) = \min_{v \in \bar{F}(t, x)} \langle v, \eta \rangle$$


$$H(t, x, \eta) = \max_{v \in \bar{F}(t, x)} \langle v, \eta \rangle$$

Invariance principles allows to write the **(HJB)** equation:

- $\text{epi}(V)$ is **weakly invariant** iff $h(t, x, \eta) \leq 0$ for all $\eta \in N_{\text{epi}(V)}^P(t, x)$;
- $\text{hypo}(V)$ is **strongly invariant** iff $H(t, x, \eta) \leq 0$ for all $\eta \in N_{\text{hypo}(V)}^P(t, x)$;
- **(HJB)** equation arises if the previous conditions hold.

INVARIANCE PRINCIPLES


$$h(t, x, \eta) = \min_{v \in \bar{F}(t, x)} \langle v, \eta \rangle$$



$$\dot{x} \in \begin{cases} 1 & x > 0 \\ [-1, 1] & x = 0 \\ -1 & x < 0 \end{cases}$$

$\{0\}$ **Weakly Invariant.**

$$H(t, x, \eta) = \max_{v \in \bar{F}(t, x)} \langle v, \eta \rangle$$




$$\dot{x} \in \begin{cases} -1 & x > 0 \\ [-1, 1] & x = 0 \\ 1 & x < 0 \end{cases}$$

$\{0\}$ **Strongly Invariant.**

INVARIANCE PRINCIPLES


$$h(t, x, \eta) = \min_{v \in \bar{F}(t, x)} \langle v, \eta \rangle$$



$$\dot{x} \in \begin{cases} 1 & x > 0 \\ [-1, 1] & x = 0 \\ -1 & x < 0 \end{cases}$$

$\{0\}$ **Weakly Invariant.**

$$H(t, x, \eta) = \max_{v \in \bar{F}(t, x)} \langle v, \eta \rangle$$



$$\dot{x} \in \begin{cases} -1 & x > 0 \\ [-1, 1] & x = 0 \\ 1 & x < 0 \end{cases}$$

$\{0\}$ **Strongly Invariant.**

$$h(t, 0, \eta) \leq 0, H(t, 0, \eta) \not\leq 0 \text{ for all } \eta \in \mathbb{R}^n.$$

HAMILTON-JACOBI-BELLMANN EQUATIONS

Theorem

V is the unique, loc. Lipschitz in \mathcal{D} , bounded below viscosity solution of the following problem:

If $(t, x) \in \mathcal{D} \cup \text{Gr}\mathcal{T}^c$,

$$\partial_t V + \liminf_{x' \xrightarrow{-\nabla_x V} x} [h(t, x', \nabla_x V)] = 0.$$

If $(t, x) \in \text{Gr}\mathcal{T}$,

$$\min \left\{ W(t, x) - V(t, x), \partial_t V + \liminf_{x' \xrightarrow{-\nabla_x V} x} [h(t, x', \nabla_x V)] \right\} = 0.$$

With the following boundary conditions:

$$V(t, x) = +\infty \text{ for all } (t, x) \notin \mathcal{D};$$

$$V(t_k, x_k) \rightarrow +\infty \text{ for all } (t_k, x_k) \rightarrow \partial\mathcal{D};$$

$$V(t_k, x_k) \rightarrow \infty \text{ for all } (t_k, x_k) \in \mathcal{D} \text{ such that } t_k \rightarrow \infty.$$

- **Validation of the circumnutation** as a mechanical reaction of roots to the soil friction;
- Estimation of **soil forces** in dynamical interactions;
- Development of a tool to support engineers in **designing efficient robots for the soil exploration**;
- Characterisation of the value function for a new class of **non-smooth optimal control problems**.

**Thank you
for your attention**